
# **Operation Guide 5436**

Your watch may differ somewhat from the one shown in the illustration.



### Crown Operations


Some water-resistant models (100 meters, 200 meters) have a screw-in crown. When you need to perform a crown operation, rotate it towards you to unscrew it. Then pull the crown out. Avoid applying undue force when pulling. The watch loses its water resistance while the crown is unscrewed. After performing a crown operation, fully screw the crown back in.



Crown

#### If your watch has a rotary bezel...

You can rotate the bezel to align its  $\checkmark$  mark with the minute hand. Then you will be able to tell how much time has elapsed since aligning the  $\checkmark$  mark.



# **Specifications**

Accuracy: ±20 seconds average per month Battery: One silver oxide battery (Type: SR920SW) Battery Life: Approximately 3 years To adjust the time setting

When the second hand is at 12 o'clock, pull the Crown out to Click 2. ÷. Rotate the Crown to change the time setting.

÷

# To change the day setting

Push the Crown back in.

| Pull the Crown out to Click 1.        |
|---------------------------------------|
|                                       |
| Rotate the Crown to set the day.      |
| · · · · · · · · · · · · · · · · · · · |
| Push the Crown back in.               |
|                                       |

## Note

Note
Take care that you set the correct AM or PM time.
When changing the time, move the minute hand four or five minutes past your final setting, and then back it up to the setting you want.

Note
The day setting uses a 31-day month. Make adjustments for months of shorter lengths.
Avoid changing the day setting between the hours of 9 p.m. and 1 a.m. Otherwise, the day setting may not change correctly at midnight.

# **CASIO**<sub>®</sub>